




Dimension: (Unit: mm)



Motor Connctions



Common Rating

Step angle	1.8°
Position accuracy	1.8±0.09°
Dielectric strength	500VAC 1min
Insulation resistance	100MOhm(500VDC)
Insulation class	B
Temp rise(Max)	80K
Radial play	Max.0.02mm(Load 450g)
Axial play	Max.0.08mm(Load 900g)

Specification:

Current/phase	0.9 A
Voltage	2.0 V
DC Resistance/phase ±10%	2.2 Ω
Inductance/phase ±20%	2.4 mH
Holding torque	0.13 N•M
Detent torque	0.018 N•M
Inertia	0.018 kg•cm ²
Weight	0.2 kg

技术要求:
1、未注形位公差按GB/T 1184-K;
2、未注尺寸公差按GB/T 1804-m。
(除非另外指定)

设计 Designed	标准化 Standardized	材料(Material):	名称(Title)	步进电机
制图 Drawn		重量(Weight)/g:	型号(Model)	28CM013-ZK MS20
校对 Proofread	审核 Checked	阶段标记(Stage Mark)	图号(DWG No.)	LS-28CM013-ZK MS20
工艺 Processed	批准 Approved		料号(Part No.)	
表单编号 Form No.	LS-QP-46-09A	版本/版次 Edition/Serial NO.	比例(Scale)	1:1
			共1页第1页 Page 1 of 1	